

# AIRBUS A300-600F

European Consortium

## Aircraft variants

<b>A300-600F</b>	Dedicated freighter model
<b>A300-600R</b>	Extended range model
<b>A300-600C</b>	Convertible passenger or freighter version
<b>A300F4-600R</b>	UPS freighter version allows carriage of extra container (22 in total) on main deck

## Noise levels (EPNdb) PW 4000 engines

Take off	88
Sideline	98.3
Approach	101.3

## General dimensions

Wingspan	44.84 m (147' 1")
Length	54.08 m (177' 5")
Height	16.54 m (54' 3")

## Freight deck/cabin dimensions

Length	33 m (109')
Max width	5 m (17')
Width at floor	N/A
Height	2.5 m (8')
Volume	265 m <sup>3</sup> (9 360 ft <sup>3</sup> )

## Freight door dimensions

Main	N/A
Forward	N/A
Aft	1.81 m x 1.7 m (5' 11" x 5' 7")
Bulk A	0.95 m x 1.14 m (3' 1½" x 3' 9")
Bulk B	N/A
Nose	5.1 m x 11.78 m (16' 9" x 38' 8")

## Weights

EOW	90 100 kg (198 600 lb)
MZF	130 000 kg (286 600 lb)
MTOW	168 000 kg (370 400 lb)
MLW	140 000 kg (308 600 lb)



## Operating data

Max cruise speed	480 kts (553 mph) 890 kph @ 7 620 m (25 000')
Fuel capacity	68 150 litres (14 990 gal) 18 000 US gal
Fuel burn p/h	4 300 kg (9 480 lb)
Runway required T/O	2 290 m (7 515')
Runway required Ldg	1 555 m (5 100')

# Long range freighter

2 turbofans • First flight 1994



**AIRBUS A300-600F**

## Payload

Maximum: 55 017 kg (121 290 lb)

Main deck: holds 9 88"/96" x 125" pallets and 6 88" x 125" pallets

Lower deck: holds 4 pallets and 10 LD3 or 22 LD3 containers.

## Additional information

- Semi-automatic cargo loading system
- Class E fire protection on main deck
- Class C fire protection on lower deck